EN · Specifications

Meteor 2202B

P/N	LN-2202B
Input Voltage	9-17 V AC/DC
Lighting source	MR16 (sold separately, max 50 W)
Socket	GU5.3 bi-pin
Working Temperature	-45 to 45 °C
Water Proof	IP65
Lens	Clear flat glass (frosted optional)
Lead Wire	72 in (1.8 m) SVT-1W, 18 AWG
Mounting	In-ground, direct burial
Gross Weight	1000 g
Certifications	cETLus
Warranty	Brass body and housing 10 years · Finish 2 years · Lamp per lamp warranty

FR · Spécifications

Meteor 2202B

No de pièce	LN-2202B
Tension d'entrée	9-17 V AC/DC
Source d'éclairage	MR16 (vendue séparément, max 50 W)
Douille	GU5.3 bi-pin
Temp. de fonctionnement	-45 à 45 °C
Niveau d'étanchéité	IP65
Lentille	Clear flat glass (frosted optional)
Fil d'alimentation	72 in (1.8 m) SVT-1W, 18 AWG
Montage	In-ground, direct burial
Poids brut	1000 g
Certifications	cETLus
Garantie	Corps et boîtier en laiton 10 ans · Fini 2 ans · Lampe selon sa garantie

© 2026 Luna Nova · LN-2202B · Warranty per LN-WAR