EN · Specifications

Telescope 2420B

P/N	LN-2420B
Input Voltage	9-17 V AC/DC
Lighting source	MR16 (sold separately, max 50 W)
Socket	GU5.3 bi-pin
Working Temperature	-45 to 45 °C
Water Proof	IP65
Lens	Clear acrylic with 360° frosted cover
Lead Wire	72 in (1.8 m) SPT-1W, 18 AWG
Mounting	8.5 in large brass ground stake
Certifications	cETLus
Warranty	Brass body and housing 10 years · Finish 2 years · Lamp per lamp warranty

FR · Spécifications

Telescope 2420B

No de pièce	LN-2420B
Tension d'entrée	9-17 V AC/DC
Source d'éclairage	MR16 (vendue séparément, max 50 W)
Douille	GU5.3 bi-pin
Temp. de fonctionnement	-45 à 45 °C
Niveau d'étanchéité	IP65
Lentille	Clear acrylic with 360° frosted cover
Fil d'alimentation	72 in (1.8 m) SPT-1W, 18 AWG
Montage	8.5 in large brass ground stake
Certifications	cETLus
Garantie	Corps et boîtier en laiton 10 ans · Fini 2 ans · Lampe selon sa garantie

© 2026 Luna Nova · LN-2420B · Warranty per LN-WAR