EN · Specifications

Shuttle 2701P

P/N	LN-2701P
Order Codes	LN-2701P-MB / LN-2701P-AB
Input Voltage	9-17 V AC/DC
Light Source	Integrated LED module
Wattage	2 / 3 / 4 W
Output Lumens	200 / 300 / 400 lm
CRI (Ra)	>= 85
Water Proof	IP65
Lens	Frosted polycarbonate
Lead Wire	72 in (1.8 m) SPT-1W, 18 AWG
Mounting	3 stainless brackets (wall, step, or capstone)
Gross Weight	650 g
Certifications	cETLus
Warranty	Brass body and housing 10 years · Integrated LED module 5 years · Finish 2 years

FR · Spécifications

Shuttle 2701P

No de pièce	LN-2701P
Codes de commande	LN-2701P-MB / LN-2701P-AB
Tension d'entrée	9-17 V AC/DC
Source lumineuse	Module DEL intégré
Puissance	2 / 3 / 4 W
Flux lumineux	200 / 300 / 400 lm
IRC (Ra)	>= 85
Niveau d'étanchéité	IP65
Lentille	Frosted polycarbonate
Fil d'alimentation	72 in (1.8 m) SPT-1W, 18 AWG
Montage	3 stainless brackets (wall, step, or capstone)
Poids brut	650 g
Certifications	cETLus
Garantie	Corps et boîtier en laiton 10 ans · Module DEL intégré 5 ans · Fini 2 ans

© 2026 Luna Nova · LN-2701P · Warranty per LN-WAR

LUNA NOVA