EN · Specifications

Utility Beam 9905 — Modular System

P/N	LN-9905
Input Voltage	9-17 V AC/DC
Light Source	Integrated LED module
Wattage	3 / 4 W
Colour Temperature	2700K / 3000K
Output Lumens	300 / 400 lm
CRI (Ra)	>= 85
Working Temperature	-45 to 45 °C
Water Proof	IP65
Lead Wire	Pre-stripped 40 in (1.0 m) UL2464, 24 AWG
Mounting	Embedded sleeve
Gross Weight	870 g
Certifications	cETLus
Warranty	Integrated LED module 5 years · See LN-WAR for full terms

FR · Spécifications

Utility Beam 9905 — Modular System

No de pièce	LN-9905
Tension d'entrée	9-17 V AC/DC
Source lumineuse	Module DEL intégré
Puissance	3 / 4 W
Température de couleur	2700K / 3000K
Flux lumineux	300 / 400 lm
IRC (Ra)	>= 85
Temp. de fonctionnement	-45 à 45 °C
Niveau d'étanchéité	IP65
Fil d'alimentation	Pre-stripped 40 in (1.0 m) UL2464, 24 AWG
Montage	Embedded sleeve
Poids brut	870 g
Certifications	cETLus
Garantie	Module DEL intégré 5 ans · Conditions complètes au LN-WAR

© 2026 Luna Nova · LN-9905 · Warranty per LN-WAR