EN · Specifications

Little Star 9907A

P/N	LN-9907A
Input Voltage	9-17 V AC/DC
Light Source	Integrated LED module
Wattage	1 W
Colour Temperature	2700K / 3000K
Output Lumens	80 lm
Beam Angle	30°
CRI (Ra)	>= 85
Working Temperature	-45 to 45 °C
Water Proof	IP67
Lens	Clear glass
Lead Wire	40 in (1.0 m) UL2464, 24 AWG
Mounting	Pre-embedded sleeve (sold separately)
Gross Weight	120 g
Certifications	cETLus
Warranty	Integrated LED module 5 years · See LN-WAR for full terms

FR · Spécifications

Little Star 9907A

No de pièce	LN-9907A
Tension d'entrée	9-17 V AC/DC
Source lumineuse	Module DEL intégré
Puissance	1 W
Température de couleur	2700K / 3000K
Flux lumineux	80 lm
Angle de faisceau	30°
IRC (Ra)	>= 85
Temp. de fonctionnement	-45 à 45 °C
Niveau d'étanchéité	IP67
Lentille	Clear glass
Fil d'alimentation	40 in (1.0 m) UL2464, 24 AWG
Montage	Pre-embedded sleeve (sold separately)
Poids brut	120 g
Certifications	cETLus
Garantie	Module DEL intégré 5 ans · Conditions complètes au LN-WAR

© 2026 Luna Nova · LN-9907A · Warranty per LN-WAR